




EXCAVATOR GRAPPLES

INCREASE EXCAVATOR PRODUCTIVITY



H23



L45



TWO MODELS FOR ALL APPLICATIONS

Rockland Excavator Grapples really get the job done! Whether it be demolition work, loading rock, clearing land, or handling trash, there is a Rockland Excavator Grapple for your application.

Rockland Excavator Grapples are designed to produce and built to last. They are built entirely out of high strength, alloy steel plate, and use the same Rockland reinforced box-frame design. Both models are equipped with replaceable wear plates at the front and rear of each tine. They both pivot on heat-treated, hardened pins and bushings.

H23 Severe Service - The H23 was designed specifically for rough applications. Its narrow, two-tine clamp and three-tine frame maximize both clamping and digging forces. It is recommended for heavy-duty demolition work, rock handling, severe land clearing jobs, and other applications that require maximum clamping, prying, and breakout forces.

L45 Light Material - The L45 is designed for handling trash, light scrap, or other light, bulky material. Its wide four-tine clamp and five-tine frame efficiently handle large loads of lighter materials for maximum loading efficiency.

All Rockland Excavator Grapples are built with the same dedication to quality that made our other products famous. We build great grapples and we back up that claim with a no nonsense, 2 year/4000 hour warranty. Increase your excavator's productivity— specify a Rockland Excavator Grapple.

H23 EXCAVATOR GRAPPLE SPECIFICATIONS

Machine Class	A	B	C	D	E	F
Excavator Weight (lbs.)	25,001 to 33,000 11343 to 14973	33,001 to 52,000 14973 to 23593	52,001 to 70,000 23594 to 31760	70,001 to 90,000 31761 to 40835	90,001 to 110,000 40835 to 49909	110,001 to 160,000 49909 to 72595
Max. Opening (")	90 2286	97 2464	115 2921	118 2997	145 3683	155 3937
Min. Opening (")	7 200	9 243	10 ^{1/2} 267	12 ^{1/2} 318	15 ^{3/8} 391	18 ^{1/2} 470
Height Closed (")	49 ^{11/16} 1262	58 ^{3/4} 1492	71 ^{7/8} 1826	74 ^{3/4} 1899	83 ^{3/8} 2118	90 ^{-1/4} 2296
Lower Jaw Width (")	32 ^{1/4} 819	45 1143	45 1143	49 ^{1/4} 1251	53 ^{1/4} 1353	60 1524
Upper Jaw Width (")	21 ^{1/4} 540	30 ^{1/2} 775	30 ^{1/2} 775	32 ^{3/4} 832	35 889	39 990
Weight (lbs.)	1520 689	2740 1243	3650 1656	5300 2404	7100 3220	7100 3220

(mm/kg)

Specifications subject to change without notice.

L45 EXCAVATOR GRAPPLE SPECIFICATIONS

Machine Class	B	C	D	E	F
Excavator Weight (lbs.)	33,001 to 52,000 14973 to 23593	52,001 to 70,000 23594 to 31760	70,001 to 90,000 31761 to 40835	90,001 to 110,000 40835 to 49909	110,001 to 160,000 49910 to 72595
Max. Opening (")	97 2464	115 2921	118 2997	145 3683	145 3683
Min. Opening (")	9 243	10 ^{1/2} 267	12 ^{1/2} 318	15 ^{3/8} 391	15 ^{3/8} 391
Height Closed (")	58 ^{3/4} 1492	71 ^{7/8} 1826	74 ^{3/4} 1899	83 ^{3/8} 2118	81 ^{1/16} 2059
Lower Jaw Width (")	55 1397	55 1397	60 1524	65 1651	84 2134
Upper Jaw Width (")	44 1118	44 1118	47 1194	50 1270	64 1626
Weight (lbs.)	3045 1381	4200 1907	5300 2406	7090 3216	8175 3711

(mm/kg)

Specifications subject to change without notice.

MOUNTING INFORMATION

Rockland Excavator Grapples mount on the stick in place of the standard bucket using standard factory pins. An optional Rockland pin and bushing kit is available that allows the grapple to be installed on more than one machine in the same weight class. The grapple is supplied with a support strut and a strut mounting bracket that must be welded to the bottom of the excavator stick.

WARRANTY

Rockland Excavator Grapples are guaranteed against failure due to defective design, materials, or workmanship for a period of two years or 4,000 hours.

Distributed by:



ROCKLAND MANUFACTURING CO.
P O BOX 5
800-458-3773

BEDFORD, PA 15522
www.rocklandmfg.com